

Single Switching Unit SSU



Compliance

All SSUs meet the following industry standards:

- BS EN 61823
- FAA specification AC 150/5345-47
- ICAO Design Manual, Part 5, Electrical Systems

The ALS SSU is available in either Fail-On or Fail-Off versions. The ALS SSUs enables the suppression of any LED or incandescent lamp from 0W to 100W that uses a 6.6A supply down to 1A. The SSU is also available in the form of a combined switching transformer with both items cast in the same encapsulated unit.

Features

- Encapsulated in a homogenous high quality polyurethane resin
- Uses 31% less energy than other switching devices when the lamps are suppressed
- Current ramping as standard, gives longer lamp life
- Interchangeable with any other manufacturers' lamp suppression unit
- Available in
 - Fail-On/Fail-Off version
 - Fail-On/Fail-On version
 - Fail-Off/Fail-Off version
- 12hr minimum water testing prior to despatch
- Ambient temperature range -20°C to +55°C
- Resistant to acid and alkaline soils, oils, fuels and de-icing fluids
- Materials used are also termite and rodent proof
- IP rating equivalent to IP68

Option

- 2 pin plug and socket control leads

Specification

- Switching signal voltages 12V to 72V DC - **Half-wave control signals must not be used**
- Switching signal current of 2mA at 48V DC
- Switching signal to transformer secondary isolation voltage of +2500V AC
- Control signal cables 3 core, 2.5mm²
- Current to the lamps is ramped up and down more slowly than the regulator changes its firing angle (150ms)
- Maximum rms voltage of 33V when open circuit

Application

- Military or civil airport AGL constant current circuits.
- Taxiway Routing
- Stop Bar Control

AGLST	Size	Weight
Compatibility		
30 – 100 Watts	L: 125mm Diameter: 65mm	1.1kg